

86" FULLY OUTDOOR DIGITAL SIGNAGE


E Series



IP Rating



High Brightness



Ultra Thin



Four Seasons



Horizontal & vertical



Tempered Glass

Keewin Display offers a premium outdoor digital signage solution with a high-brightness LCD display, integrated high-temperature LCD, self-cooling design, and AG coating glass for enhanced visibility. This signage is easy to integrate into custom frames and doesn't require additional waterproofing or cooling measures, making it an excellent choice for outdoor advertising needs.



Technical Specifications

LCD Display

| | |
|----------------------------------|----------------------------------|
| Size | 86 |
| Active Display Area (H x V mm) | 1896 x 1067 |
| Resolution | 3840 x 2160 |
| Brightness | 3000 nits |
| Aspect Ratio | 16 : 9 |
| Backlight Adjustment | Automatic (Ambient Light Sensor) |
| Viewing Angle | 178°/178° |
| Backlight Configuration | Direct LED |
| Operation Life (hours) | 50,000 |

Certificate

CE-EMC
CE-LVD
ROHS
IP66

Mechanical

| | |
|--------------------|---|
| Enclosure Material | Aluminum |
| Finishing | Fine Grain Powder Coating |
| Colour | Black (Ral 9005) |
| Glass | Tempered Glass,Back Painted Pantone Black C |

Optional

Touch
Android
Computer
Camera
NFC
RFID
Ultrasonic sensor

Power

| | |
|-----------------------|-------------------------------------|
| AC Input | 110 VAC / 220 VAC±10% , 50 to 60 Hz |
| Power Consumption (w) | TBD |

Environment

| | |
|-----------------------|---------------|
| IP Rating | IP66 |
| Operating Environment | Fully Outdoor |
| Operating Temperature | -30°C~50°C |
| Operating Humidity | 5%~98% |
| Operating Altitude | < 2000m |

Media

(HDMI In) Standard

| | |
|---------------------|---|
| HDMI Input | HDMI (x 1), 480i, 480p, 720p, 1080i , 1080p , 2160p |
| Analog Audio Output | 3.5mm Headphone Jack (x1) |

Mechanical

W x H x D **1991 x 1162 x 120 mm**
Net Weight **TBD**

