

ML1050STi

Ultra-compact short throw LED projector



- HD Ready and LED technology - Great for movies, Gaming, PC-free presentations, Signage Displays, Simulations and more
- Short throw lens with auto focus and Auto Keystone
- Feature packed - Built in media player, optional wireless, HDMI, MicroSD and built in speaker
- Ultra compact and lightweight - only 14oz.

Perfect for meetings, presentations or movies on-the-go. This tiny projector weighs just 14oz. and comes with a convenient carry bag.

Road Warrior can project laptop free presentations using the built-in media player, native office viewer, microSD* card slot and USB connection or present wirelessly from a mobile device using the free Display Share app and optional dual-band wireless USB adapter (EZC-USB).

You can even use the ML1050ST+ for digital signage applications, as the projector can be mounted in virtually any orientation. For Home This compact projector is ideal for watching HD movies directly from a MicroSD* card, USB stick or using the built-in memory.

And with a quick response time of 16ms input lag, this entertainment projector gives gamers the competitive advantage.

Specifications

The following specifications are preliminary and subject to change without notice

Display/image

Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	1000/535
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	90%
Screen size	1.27m ~ 2.54m (50" ~ 100") diagonal

Lamp info

Light source type	LED
LED life	20,000 hours

Optical

Throw ratio	0.8:1
Projection distance	0.86m - 1.72m / 33.86" - 67.72"
Zoom type	Fixed
Focal length	8.02mm/0.32"
Native offset	100%

Connectivity

Connections	Inputs 1 x HDMI 1.4b, 1 x microSD card, 1 x USB-A reader Outputs 1 x Audio 3.5mm Control 1 x RS232 (via mini USB connector)
-------------	--

General

Noise level (min)	22dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
24/7 operation	Yes
Operating conditions	0°C~40°C/41°F~95°F, max altitude 2500M/8202.5ft, max humidity 85%
Remote control	Card style
Speaker count	1
Watts per speaker	2W
In the box	Carry bag Universal I/O cable AC power cord Remote control 1x CR2032 Battery Basic user manual 1x RS232 Mini-USB adaptor
Operating system compatibility	Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+
Input lag	16.00ms
Optional wireless models	EZC-USB

Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	23W
Power consumption (max)	67W

Weight and dimensions

Dimensions (W x D x H)	112 x 123 x 57 mm / 4.41" x 4.84" x 2.24"
Gross weight	1.2 kg / 2.65 lbs
Net weight	0.4 kg / 0.88 lbs
UPC	796435 44 744 1

