OUT OF STOCK

PowerLite 2265U Wireless Full HD WUXGA 3LCD Projector

Contact Us 800.463.7766

Mon-Fri 6am-8pm, Sat 7am-4pm PT



The bright, wireless, Full HD WUXGA projector with advanced security.

A portable powerhouse, the PowerLite 2265U wireless projector brings brilliant high-definition images to virtually any boardroom or conference room. This bright performer features native WUXGA resolution for displays up to 300", Full HD 1080p support for true-to-life displays, and versatile connectivity options. Offering 3x Higher Color Brightness[†] than competitive models, Epson® 3LCD projectors ensure vivid images. With 5,500 lumens of color brightness and 5,500 lumens of white brightness¹, the 2265U shines bright in a variety of lighting conditions. It delivers great contrast for impactful presentations. Featuring HDBaseT for easy installation, the projector also offers enterprise-level wireless security and secure screen mirroring from mobile devices.

Projection System: High-aperture Epson 3LCD, 3-chip technology

Native Resolution: WUXGA resolution (1920 x 1200)

Color Brightness: 5500 lumens¹ White Brightness: 5500 lumens¹ Throw Distance Calculator

Model: V11H814020

OUR PRICE :

\$2,299.00

Mail-in Rebate: Free Lamp

Exclusive Offer

Education Pricing

1 of 4 3/8/2018, 1:55 PM

★★★★ Write a review

Overview

Bright and Colorful

Features 5500 lumens of color brightness (color light output)¹ and 5500 lumens of white brightness (white light output)¹.

Auto Screen Fit

Easily and quickly adjust the image to fit the screen.

Wireless Ready

Includes a high-speed LAN module for wireless connectivity

WUXGA Resolution

1920 x 1200 Full HD widescreen resolution

HDBaseT

Combines HDMI, ethernet and RS-232 into one cable

- Far more accurate color with Epson 3LCD, 3-chip technology for 3x Higher Color Brightness[†] and up to 3x Wider Color Gamut² than competitive DLP projectors
- Look for two numbers
 - o 5,500 lumens² Color Brightness for more accurate, vivid color
 - o 5,500 lumens² White Brightness for well-lit rooms
- Bright, widescreen images up to 300" WUXGA resolution (1920 x 1200); Full HD 1080p support
- Remarkable sharpness and detail 15,000:1 contrast ratio; added clarity when displaying text and graphics
- Stream content from your smartphone or tablet full mirroring capabilities from your mobile device via MHL®; or, wirelessly using Miracast®
- Versatile in every way small enough for travel, but easy to install with HDBaseT, plus a full array of connectivity options, including 2x HDMI®
- Robust integrated wireless networking enterprise-level security for peace of mind; compatible with WEP, WPA, WPA2-PSK and WPA2-EAP security protocols
- Split Screen^{3/sup> feature} simultaneously project two images (video or still) side-by-side from two different sources
- Remote management and control tools included software allows for remote monitoring and control of Epson networked projectors; also compatible with Crestron® RoomView®
- Long-lasting lamp up to 10,000 hours in ECO Mode⁴

Specifications

Specifications Projector:

Projection System:

3LCD, 3-chip technology

Projection Method:

Front/rear/ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

2,304,000 dots (1920 x 1200) x 3

Color Brightness - Color Light Output:

5,500 lumens

White Brightness - White Light Output:

5,500 lumens

Aspect Ratio:

2 of 4 3/8/2018, 1:55 PM

16:10

Native Resolution:

1920 x 1200 (WUXGA)

Supported Maximum Transferred Resolution:

1920 x 1080 (1080p)

Resize:

640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050

Lamp Type:

300 W UHE

Lamp Life:

Up to 10,000 hours (ECO Mode), Up to 5,000 hours (Normal Mode)

Throw Ratio Range:

1.38 (Zoom: Wide), 2.28 (Zoom: Tele)

Size - projected distance:

50" - 300" (1.46 m - 8.95 m) (Zoom: Wide)

Keystone Correction:

Vertical: ± 30 degrees, Horizontal: ± 20 degrees

USB Plug 'n Play:

Projector is compatible with PC and Mac® computers

Contrast Ratio:

Up to 15,000:1

Color Reproduction:

Up to 1.07 billion colors

General:

Weight:

10.4 lb (4.6 kg)

Security:

Kensington-style lock provision

Operating Temperature:

41 $^{\circ}$ to 95 $^{\circ}F$ (5 $^{\circ}$ to 35 $^{\circ}C)$

Projection Lens:

Type:

Optical Zoom (Manual)/Focus (Manual)

F-number:

1.5 - 2.0

Focal Length:

 $23.0 - 38.4 \; \text{mm}$

Zoom Ratio:

1.0 - 1.6

Projector Details:

Input Signal:

Auto, RGB, and Component

Interfaces:

- 1x HDBaseT
- 2x HDMI® (1 in common with MHL®)
- Computer: 1x D-sub 15 pin
- Video: 1x RCA
- Audio-in: 3x Mini stereo
- Audio-in: 1x RCA (L & R)

3 of 4 3/8/2018, 1:55 PM

Network: 1x RJ-45, 100Mbps Serial: 1x RS-232cMonitor Out: 1x D-sub 15 pin

Speaker: 16 W (mono)

Fan Noise:

39 dB (Normal Mode), 29 dB (ECO Mode)

Projector Dimensions:

Including feet:

14.85" x 11.48" x 4.93" (W x D x H)

Excluding feet:

14.85" x 11.46" x 4.33" (W x D x H)

Remote Control:

Features:

Brightness, Contrast, Tint, Saturation, Sharpness, Input signal, Sync, Tracking, Position, Color temperature, Volume

Operating Distance:

26.2 ft (8 m)

Operating Angle:

Right/left: ± 45 degrees Upper/lower: +45 to -15 degrees

Power:

Power Supply Voltage:

 $100 - 240 \text{ V AC } \pm 10\%, \, 50/60 \text{ Hz}$

Power Consumption:

- 450 W (Normal Mode)
- 340 W (ECO Mode)
- 2.4 W Standby (Communication On)
- 0.21 W Standby (Communication Off)

Copyright © 2000-2018 Epson America, Inc.

4 of 4